

CALIBRATION

Kuhnle

2T9T214316B089564
5400 U.S.G.

T-664 T-666
T-665 T-667

LIQUID HEIGHT	VOLUME Gal US.	LIQUID HEIGHT	VOLUME Gal US.	LIQUID HEIGHT	VOLUME Gal US.
1/2	7	20	1 642	39 1/2	3 904
1	21	20 1/2	1 698	40	3 959
1 1/2	38	21	1 754	40 1/2	4 014
2	58	21 1/2	1 811	41	4 069
2 1/2	80	22	1 869	41 1/2	4 123
3	105	22 1/2	1 926	42	4 176
3 1/2	133	23	1 984	42 1/2	4 229
4	162	23 1/2	2 041	43	4 281
4 1/2	192	24	2 100	43 1/2	4 333
5	225	24 1/2	2 158	44	4 385
5 1/2	258	25	2 216	44 1/2	4 435
6	294	25 1/2	2 275	45	4 486
6 1/2	330	26	2 334	45 1/2	4 535
7	368	26 1/2	2 392	46	4 584
7 1/2	407	27	2 451	46 1/2	4 632
8	447	27 1/2	2 510	47	4 679
8 1/2	488	28	2 569	47 1/2	4 726
9	530	28 1/2	2 628	48	4 772
9 1/2	573	29	2 688	48 1/2	4 817
10	617	29 1/2	2 747	49	4 861
10 1/2	662	30	2 806	49 1/2	4 904
11	708	30 1/2	2 865	50	4 946
11 1/2	755	31	2 924	50 1/2	4 987
12	802	31 1/2	2 983	51	5 028
12 1/2	850	32	3 042	51 1/2	5 067
13	899	32 1/2	3 101	52	5 104
13 1/2	949	33	3 160	52 1/2	5 141
14	999	33 1/2	3 218	53	5 176
14 1/2	1 050	34	3 277	53 1/2	5 210
15	1 101	34 1/2	3 335	54	5 242
15 1/2	1 153	35	3 393	54 1/2	5 273
16	1 205	35 1/2	3 451	55	5 302
16 1/2	1 258	36	3 508	55 1/2	5 329
17	1 312	36 1/2	3 566	56	5 354
17 1/2	1 366	37	3 623	56 1/2	5 377
18	1 420	37 1/2	3 680	57	5 397
18 1/2	1 475	38	3 736	57 1/2	5 414
19	1 530	38 1/2	3 793		
19 1/2	1 586	39	3 849		